



LUBINOL GTS

SAE 20W-50

Maximum Performance
Multigrade Motor Oil
Motor Oil.

Description and Properties

LUBINOL GTS 20W-50 is a high-performance motor oil for modern heavily stressed diesel engines inclusive turbo charger. This makes it being excellent provider for mixed-fleet, whenever the viscosity-level 20W50 is indicated or required because of the climatical conditions.

Benefits

LUBINOL GTS SAE 20W-50 gives following advantages:

- Excellent thermal/oxidative stability reduces sludge built-up und deposits
- Allows maximum oil drain intervals by highest TBN-reserve.
- Minimizes efficiently bore polishing
- Reduces oil aging, even at high temperatures.
- Best seal and elastomer compatibility.
- An all-seasons oil for mixed-fleet in warm and tropical climate.

LUBINOL GTS SAE 20W-50 is especially recommended for fleets operating in severe on and off-highway service applications (trucks and busses) and for construction vehicles.

Specification / Recommendation

ACEA E7

API CI-4 / SL

MB 228.3 & 229.1

MAN M 3275

MTU Typ 2

Nominal Values

LUBINOL GTS 20W-50	Unit	Value	Method
Density at 15°C	kg/m ³	882	DIN 51 757
Viscosity at 40°C	mm ² /s	147,50	DIN 51 562
Viscosity at 100°C	mm ² /s	17,70	DIN 51 562
Viscosity Index		132	DIN ISO 2909
CCS at -25°C	mPa.s	5900	DIN 51 377
Pourpoint	°C	-33	DIN ISO 3016
Flashpoint	°C	234	DIN ISO 2592
TBN	mg KOH/g	10,8	DIN ISO 3771

Specification variations in these characteristics may occur the instructions of manufacturer must be regarded. Further informations to be available by MSDS.