



LUBINOL ATF DSG AUTOMATIC TRANSMISSION FLUID.

Product Description

LUBINOL ATF DSG is recommended for Audi- and VW-Double Clutch Transmission (DSG), that the ATF oil with No. TL 521 82 and TL 525 29 needs

Properties

LUBINOL ATF DSG affords following benefits:

- extremely high wear resistance
- high thermal stability
- excellent viscosity-temperature behavior
- low pour point
- foamless, even under difficult conditions
- high oxidation stability
- high load-carrying capacity
- optimum friction characteristics
- Neutral to metals and sealing materials

Specification / Recommendation

Audi / Volkswagen / Seat / Skoda - G 052 182 A2/A6 (TL 52 182), G 052 529 A2/A6 (TL 52 529)

BMW - DCTF-1 (83 220 440 214), MTF-LT-5 (83 22 2167 666), 83 22 0397 244, 83 22 2147 477

Bugatti Veyron

Citroen / Peugeot- 6DCT451 (PSA 9734.S2)

Chrysler Powershift 6-Speed (Getrag), 68044345 EA & GA

Ferrari - TF DCT-F3

Ford/Nissan Powershift 6-Speed (GFT), Ford - WSS-M2C-936-A, WSS-M2C-200-D2

Mercedes Benz - MB 236.25, MB 236.21

Mitsubishi - Diamond Queen SSTF-1, TC-SST 6-Speed (GFT)

Renault EDC 6-Speed (Getrag), Renault - BOT 450

Porsche - 043 207 29, 043 207 30, 000 043 20, 999 917 080 00

Volvo Powershift 6-Speed (GFT)/1161838/1161839

Nominal Values

LUBINOL ATF DSG	Unit	Value	Method
Density at 15	kg/m ³	854	DIN 51 757
Viscosity at 40°C	mm ² /s	40	DIN 51 562
Viscosity at 100°C	mm ² /s	8	DIN 51 562
Viscosity Index		178	DIN ISO 2909
Dynamic Viscosity at -40°C	mPa.s	< 18.000	DIN 51 938
Pourpoint	°C	-45	DIN ISO 3016
Flash Point	°C	> 200	DIN ISO 2592

Specification variations in these characteristics may occur the instructions of manufacturer must be regarded. Further informations to be available by MSDS.