



LUBINOL ATF MULTI-HV

AUTOMATIC TRANSMISSION FLUID.

Product Description

LUBINOL ATF MULTI HV fluid is an Automatic Transmission Fluid which is made by multi-vehicle anti-shudder additive technology optimized for passenger car applications.

Application

LUBINOL ATF MULTI HV is used in an extensive range of European and American passenger car service fill applications, it also can be used in commercial vehicle applications and power steering.

Properties

LUBINOL ATF MULTI - HV affords following benefits:

- Exceptional oxidation behaviour
- Anti-shudder durability.
- smoother shifts over a long period of time
- excellent anti-rust properties
- low foaming tendency

Specification / Recommendation

GM DEXRON II / II-D / II-E / III-G / III-H

Allison C-4, TES-295, TES-389
BMW/Mini P/N 81 22 9 400 272/275
BMW/Mini P/N 81 22 9 407 858/859
BMW/Mini P/N 83 22 0 024 249/359
BMW/Mini P/N 83 22 0 026 922 (BMW 7045 E)
BMW/Mini P/N 83 22 0 402 413
BMW/Mini P/N 83 22 0 403 248/249
BMW/Mini P/N 83 22 7 542 290
BMW/Mini P/N 83 22 9 407 765 (BMW LA 2634)
Chrysler/Dodge/Jeep ATF+2/ATF+3/ATF+4
Chrysler/Dodge/Jeep AS68RC ATF
Chrysler/Dodge/Jeep SP-III
Daimler/Mercedes MB 236.3, 236.5, 236.6, 236.7
MB 236.8, 236.9, 236.10, 236.91
FORD WSS-M2C919-E (Mercon V)
FORD/Lincoln/Mercury P/N XT-2-QDX [M]
FORD/Lincoln/Mercury P/N XT-2-QSM [Syn]
FORD/Lincoln/Mercury P/N XT-5-QM or -DM [V]
FORD/Lincoln/Mercury P/N XT-8-QAW [Premium]
FORD/Lincoln/Mercury P/N XT-9-QMM5 [FNR5]
FORD/Lincoln/Mercury WSS-M2C922-A1
GM/GMC/Opel/Saturn P/N 19 40 700/767
VW/Audi G 052 025 A2, G 052 055
VW/Audi G 052 162 (A1, A2)
VW/Audi G 052 990 (A2), G 055 025 (A2)
VW/Audi US 000 162

GM/GMC/Opel/Saturn P/N 21005966 (transaxle)

GM/GMC/Opel/Saturn P/N 22717466
GM/GMC/Opel/Saturn P/N 88900925/9986195
GM/GMC/Opel/Saturn T-IV, Type A Suffix A
Jaguar JLM 20238 / 20292 / 21044 / K17
Jaguar WSS-M2C922-A1
Aisin Warner JWS 3309
Land Rover Texaco ETL-7045E
MAN 339 A
Mercon V
Mobil ATF 3309
Porsche P/N 000 043 204 41
Porsche P/N 000 043 205 09
Porsche P/N 999 917 547 00 (A2)
PSA Peugeot Citroen P/N Z 000169756
Renault Matic D2
Renk Genuine Oil
Saab 3309 - T-IV
Shell 3403-M115, LA 2634
Texaco ETL 7045E / 8072B, N402
Voith H55.6335.XX
Voith Svc Bltn # 013 / 118
Volvo P/N 1161521
Volvo P/N 1161540 / 1161640
Volvo P/N 1273,41
ZF TE-ML 11A / 11B

Nominal Values

LUBINOL ATF MULTI - HV	Unit	Value	Method
Density at 15	kg/m ³	850	DIN 51 757
Colour		Red	Visual
Viscosity at 40°C	mm ² /s	38,20	DIN 51 562
Viscosity at 100°C	mm ² /s	7,00	DIN 51 562
Viscosity Index		150	DIN ISO 2909
Pourpoint	°C	-45	DIN ISO 3016
Flash Point	°C	228	DIN ISO 2592

Specification variations in these characteristics may occur the instructions of manufacturer must be regarded. Further informations to be available by MSDS.