



# LUBINOL GEAR BOX 4 MX 75W-80

Semi synthetic Standard Transmission Oil.

## Product Description

**LUBINOL GEAR BOX 4 MX 75W-80** is made from high quality HC-synthetic base oils. In combination with a modern additive-package there is achieved a performance level which has to be described as follows:

Benefits to be high lightened:

- Excellent high pressure- and wear protection properties
- Very good properties in corrosion- and rust protection
- Low foaming tendency and excellent aging stability
- High viscosity index and low pour point care for easy gear changing even at lot temperatures.
- Reduced oil consumption and extended oil drain intervals

## Application

**LUBINOL GEAR BOX 4 MX 75W-80** is used for the lubrication of synchronized and non-synchronized standard transmissions. Especially it is recommended for commercial vehicles, which are furnished with BMW, VW and Mercedes Benz manual transmissions.

## Specification

API GL-4	VW G052 512, G052 178, G052 527
BMW MTF LT-1/-2/-3/-4	VW G052 532, G052 171, G052 726
FORD WSS-M2C200-D2	VW G055 726, G052 725, G060 726
MB 235.10	VW G 009 317
PSA B 71 2330 / 9730 A2/A8	Toyota JWS 227
Volvo 97308 / 97309	Special Honda MTF/MTF-II

## Nominal Values

LUBINOL GEAR BOX 4 MX 75W-80	Unit	Value	Method
Density at 15	kg/m <sup>3</sup>	855	DIN 51 757
Viscosity at 40°C	mm <sup>2</sup> /s	51,20	DIN 51 562
Viscosity at 100°C	mm <sup>2</sup> /s	9,1	DIN 51 562
Viscosity Index		161	DIN ISO 2909
Pourpoint	°C	-42	DIN ISO 3016
Flash Point	°C	215	DIN ISO 2592

Specification variations in these characteristics may occur the instructions of manufacturer must be regarded. Further informations to be available by MSDS.