



LUBINOL GF SAE 0W-16

Fully Synthetic Fuel
Efficient Engine Oil.

Product Description

LUBINOL GF SAE 0W-16 is a high performance Fully Synthetic engine oil, which especially is designed for the most advanced gasoline engines of passenger cars, which are operated with low viscosity fuel saving engine oils. It is suitable for use in all types of modern vehicles where this viscosity grade is recommended. This includes high-performance turbo-charged, supercharged gasoline multi-valve fuel injected engines found in passenger cars and light vans.

LUBINOL GF SAE 0W-16 is designed on base of synthetic oils only. It persuades by an excellent lubricity and shows outstanding properties and benefit and meets and exceeds OEM specifications for low viscosity; and maximum fuel economy:

- stable lubrication film at all operation conditions
- outstanding cold starting properties even at low temperatures
- long motor life by complex wear protection and cleanliness from cylinder head down to oil sump
- low oil consumption and high fuel efficiency.
- lower environmental impact by reduced exhaust gas emissions and long oil drain intervals

Specifications / Recommendation

API SP

ILSAC GF-6B

Nominal Values

LUBINOL GF SAE 0W-16	Unit	Value	Method
Density at 15°C	kg/m ³	846	DIN 51 757
Viscosity at 40°C	mm ² /s	35,8	DIN 51 562
Viscosity at 100°C	mm ² /s	7,00	DIN 51 562
Viscosity Index		161	DIN ISO 2909
CCS at -35°C	mPa.s	5070	DIN 51 377
Pourpoint	°C	-45	DIN ISO 3016
Flashpoint	°C	226	DIN ISO 2592
TBN	mg KOH/g	8.2	DIN ISO 3771

Specification variations in these characteristics may occur the instructions of manufacturer must be regarded. Further informations to be available by MSDS.