



# LUBINOL GF SAE 0W-20

Fully Synthetic Fuel  
Efficient Engine Oil.

## Product Description

**Lubinol GF SAE 0W-20** has been specially developed for the most modern generation of downsizing engines. The special combination of base oils and additives helps to significantly reduce the so-called LSPI (low speed pre-ignition). With the LSPI, the gasoline-air mixture ignites spontaneously in the combustion chamber before the ignition spark occurs. This can lead to engine knocking and serious engine damage. Pollution inside the engine plays a role as well as poor fuel quality. Due to the LSPI problem, this combination of base oil and additives has been developed and is prescribed by Opel and General Motors for certain models.

**Lubinol GF SAE 0W-20** is the suitable engine oil and meets the new and tightened General Motors Specification Dexos 1 Generation 2.

The product has been developed exclusively for gasoline engines and is not suitable for diesel engines.

## Specifications / Recommendation

API SP  
ILSAC GF-6A  
GM dexos1 Gen 2  
Isuzu, Mazda

Chrysler MS-6395, Daihatsu  
Ford WSS-M2C925-A/-B  
Toyota, Honda, Lexus, Kia  
Nissan, Subaru, Suzuki

## Nominal Values

LUBINOL GF SAE 0W-20	Unit	Value	Method
Density at 15°C	kg/m <sup>3</sup>	852	DIN 51 757
Viscosity at 40°C	mm <sup>2</sup> /s	47,5	DIN 51 562
Viscosity at 100°C	mm <sup>2</sup> /s	8,30	DIN 51 562
Viscosity Index		172	DIN ISO 2909
CCS at -30°C	mPa.s	5810	DIN 51 377
Pourpoint	°C	-45	DIN ISO 3016
Flashpoint	°C	222	DIN ISO 2592
TBN	mg KOH/g	8.5	DIN ISO 3771

Specification variations in these characteristics may occur the instructions of manufacturer must be regarded. Further informations to be available by MSDS.