



LUBINOL LB SAE 20W-50

High Performance Motor Oil for passenger Cars

Product Description

Lubinol LB SAE 20W-50 is a high-performance crankcase oil to be used in passenger cars and light duty vehicles. It can be recommended for the consumption-optimised modern gasoline engine as well as for the high-output turbo charged diesel engine.

Product Benefits

Lubinol LB SAE 20W50 is a motor oil, blended from synthetic and mineral base oils and most modern additives. The excellent wear protection and the very good detergency/dispersancy, which efficiently control sludge build-up, have to be highlighted. Because of the multigrade properties based on the viscosity range 20W50 the oil especially is recommended for all-season use in warm and in tropical climates.

Specifications

API SL / CF

Nominal Values

LUBINOL LB SAE 20W-50	Unit	Value	Method
Density at 15°C	kg/m ³	891	DIN 51 757
Viscosity at 40°C	mm ² /s	170	DIN 51 562
Viscosity at 100°C	mm ² /s	18,20	DIN 51 562
Viscosity Index		119	DIN ISO 2909
CCS at -15°C	mPa.s	9350	DIN 51 377
Pourpoint	°C	-21	DIN ISO 3016
Flashpoint	°C	224	DIN ISO 2592
TBN	mg KOH/g	7,2	DIN ISO 3771

Specification variations in these characteristics may occur the instructions of manufacturer must be regarded. Further information to be available by MSDS.