



LUBINOL LFD

SAE 15W-40

Multigrade engine oils

Product Description

Lubinol LFD SAE 15W-40 engine oils are produced with mineral base stocks and selected additives. The dispersancy provides a clean engine and prevents sludge built-up. Additionally, the additives assure protection against thermal oxidation, corrosion and wear.

Product Benefits

Lubinol LFD SAE 15W-40 are economical crankcase oils, and they may be used for passenger cars gasoline and diesel engines as well. They are providing performance reserves even at high loading and care for long engine life.

Specifications

API SF / CD

Nominal Values

| LUBINOL LFD SAE 15W-40 | Unit | Value | Method |
|------------------------------|--------------------|-------|--------------|
| Density at 15°C | kg/m ³ | 882 | DIN 51 757 |
| Kinematic viscosity at 40°C | mm ² /s | 103 | DIN 51 562 |
| Kinematic viscosity at 100°C | mm ² /s | 14,0 | DIN 51 562 |
| Viscosity index | | 139 | DIN ISO 2909 |
| Dynamic viscosity at -20°C | mPa.s | 6500 | DIN 51 377 |
| Dynamic viscosity at -15°C | mPa.s | - | DIN 51 377 |
| Pourpoint | °C | -33 | DIN ISO 3016 |
| Flash point | °C | 222 | DIN ISO 2592 |

Specification variations in these characteristics may occur the instructions of manufacturer must be regarded. Further information to be available by MSDS.