



LUBINOL LSS

SAE 10W-40

High Performance Low Friction Oil.

Product Description

Lubinol LSS SAE 10W-40 is a semi-synthetic low friction oil to be used in passenger cars gasoline and diesel engines. It is produced by blending high quality synthetic components and mineral base stocks and additives of most progressive technology. Suitable also under severe operating conditions in modern passenger car engines, turbo- or non-turbo.

Product Benefits

Lubinol LSS SAE 10W40 by its optimized formulation provides lowered fuel-and oil consumption. Because of its extended viscosity range the all seasons use is possible. The dispersing power, expressed by the performance level of this product, prevents deposits and plugging in the oil circuit and thus keeps the engine clean. Modern oxidation inhibitors extend the service life of the oil and the optimal wear protection cares for long engine life.

Specifications / Recommendation

ACEA A3- / B4-08

API SL / CF

VW 505 00

MB 229.1

Nominal Values

LUBINOL LSS SAE 10W-40	Unit	Value	Method
Density at 15°C	kg/m ³	872	DIN 51 757
Viscosity at 40°C	mm ² /s	88	DIN 51 562
Viscosity at 100°C	mm ² /s	13,1	DIN 51 562
Viscosity Index		149	DIN ISO 2909
CCS at -25°C	mPa.s	6650	DIN 51 377
Pourpoint	°C	-33	DIN ISO 3016
Flashpoint	°C	210	DIN ISO 2592
TBN	mg KOH/g	8,5	DIN ISO 3771

Specification variations in these characteristics may occur the instructions of manufacturer must be regarded. Further information to be available by MSDS.