



LUBINOL MOTORBIKE SAE 10W-40

High Performance
Multigrade oil for
Motorcycles.

Product Description

LUBINOL MOTORBIKE SAE 10W40 is a high performance special engine oil for all motor cycles with air- and water-cooled 4-stroke engines of highest output. It is the ideal partner for all sportive motor-cycles, on all roads and off-road.

The high capacity is assured by a combination of high quality base oils with successfully tested additives.

LUBINOL MOTORBIKE SAE 10W40 offers

- optimal lubrication in motor and in gear and assured functionality of wet clutches even at extreme operation conditions and continuous use.
- Outstanding motor cleanliness, especially at pistons and valves.
- good cold-starting properties

Specification

ACEA A3
API SN
JASO MA2

Nominal Values

LUBINOL MOTORBIKE SAE 10W40	Unit	Value	Method
Density at 15	kg/m ³	863	DIN 51 757
Viscosity at 40°C	mm ² /s	79,5	DIN 51 562
Viscosity at 100°C	mm ² /s	15,1	DIN 51 562
Viscosity Index		161	DIN ISO 2909
CCS at -30°C	mPa.s	5590	DIN 51 377
Pourpoint	°C	-39	DIN ISO 3016
Flash Point	°C	232	DIN ISO 2592
TBN	mg KOH/g	10,5	DIN ISO 3771

Specification variations in these characteristics may occur the instructions of manufacturer must be regarded. Further information to be available by MSDS.