



# LUBINOL MOTORBIKE SAE 10W-60

High Performance  
Multigrade oil for  
Motorcycles.

## Product Description

**LUBINOL MOTORBIKE SAE 10W60** is a high performance special engine oil for all motor cycles with air- and water-cooled 4-stroke engines of highest output. It is the ideal partner for all sportive motor-cycles, on all roads and off-road.

The high capacity is assured by a combination of high quality base oils with successfully tested additives.

### LUBINOL MOTORBIKE SAE 10W60 offers

- optimal lubrication in motor and in gear and assured functionality of wet clutches even at extreme operation conditions and continuous use.
- Outstanding motor cleanliness, especially at pistons and valves.
- good cold-starting properties

## Specification

ACEA A3-04  
API SN  
JASO MA2

## Nominal Values

LUBINOL MOTORBIKE SAE 10W60	Unit	Value	Method
Density at 15	kg/m <sup>3</sup>	860	DIN 51 757
Viscosity at 40°C	mm <sup>2</sup> /s	169	DIN 51 562
Viscosity at 100°C	mm <sup>2</sup> /s	24,5	DIN 51 562
Viscosity Index		178	DIN ISO 2909
CCS at -30°C	mPa.s	6470	DIN 51 377
Pourpoint	°C	-36	DIN ISO 3016
Flash Point	°C	218	DIN ISO 2592
TBN	mg KOH/g	8,3	DIN ISO 3771

Specification variations in these characteristics may occur the instructions of manufacturer must be regarded. Further information to be available by MSDS.