



LUBINOL PSS SAE 15W-40

High Performance Low
Friction Oil.

Product Description

Lubinol PSS SAE 15W-40 is a multigrade motor oil to be used in passenger cars gasoline and diesel engines. It is produced by blending high quality base oils and additives of most progressive technology. Suitable also under severe operating conditions in modern passenger car engines, turbo- or non-turbo charged.

Product Benefits

Lubinol PSS SAE 15W40 by its optimized formulation provides lowered fuel- and oil consumption. Because of its extended viscosity range the all seasons use is possible.

The dispersing power, expressed by the performance level of this product, prevents deposits and plugging's in the oil circuit and thus keeps the engine clean. Modern oxidation inhibitors extend the service life of the oil and the optimal wear protection cares for long engine life.

Specifications / Recommendation

ACEA A3/ B4

API SL / CF

VW 505 00

MB 229.1

Nominal Values

LUBINOL PSS SAE 15W-40	Unit	Value	Method
Density at 15°C	kg/m ³	873	DIN 51 757
Viscosity at 40°C	mm ² /s	115	DIN 51 562
Viscosity at 100°C	mm ² /s	15,3	DIN 51 562
Viscosity Index		140	DIN ISO 2909
CCS at -20°C	mPa.s	5380	DIN 51 377
Pourpoint	°C	-42	DIN ISO 3016
Flashpoint	°C	230	DIN ISO 2592
TBN	mg KOH/g	10,1	DIN ISO 3771

Specification variations in these characteristics may occur the instructions of manufacturer must be regarded. Further information to be available by MSDS.